



|   |  |   |                     |
|---|--|---|---------------------|
|  | <b>CAMBODIAN CHEMICAL SUPPLY CO., LTD.</b> |   | Doc No: TDS-PRD-009 |
|   | Doc Name                                   | <b>MAX EXTRA E Technical Data Sheet</b> | Revised No: 0       |
|   | Doc Type                                   | TDS                                     | Page: <b>2 of 3</b> |

|                             |  |   |
|-----------------------------|--|---|
|                             | <b>Recommended Dry Film Thickness Per Coat</b> | 28 ± 3 μ<br><b>Reference:</b><br>- Hiding Power over 75%  |
|                             | <b>Topcoat Interval</b>                        | 2 hours @ 30 °C   |
|                             | <b>Practical Coverage</b>                      | 11 m <sup>2</sup> / liter/ coat   |
|                             | <b>Packing Size</b>                            | 18 Liters   |
| <b>INSTRUCTION FOR USES</b> | <b>Surface Preparation</b>                     | Ensure that the surfaces are free from loose particles, dirt, dust, grease, oil, wax. Make good for any surface defected, clean thoroughly and dry.   |
|                             | <b>Application Methods</b>                     | <b>By using Roller / Soft-Brush</b><br>Thin with some 10% of clean water and apply by using Roller and/or Soft-Brush.<br><br><b>By Using Air Spray</b><br>Dilute the paint with 20% of clean water. |
|                             | <b>Previously Painted Surface</b>              | Remove all unstable paint film, loose chalk, dust and other foreign matters. Treat surface with Cam-Paint Penetrate Primer PROTAN™ to strengthen substrate condition.                               |

| Sequence           | Complement Product |                 | No of Coat | For Loose Substrate |
|--------------------|--------------------|-----------------|------------|---------------------|
|                    | <i>Exterior</i>    | <i>Interior</i> |            |                     |
| <b>Plaster</b>     | VIMEAN<br>SOR      | VIMEAN<br>SOR   | 2 or 3     |                     |
| <b>Primer</b>      | MAX<br>EXTRA E     | MAX<br>EXTRA E  | 1          | PROTAN              |
| <b>Finish Coat</b> | SARIKA/VITAL       |                 | 2 or 3     |                     |

|   |  |   |                     |
|---|--|---|---------------------|
|  | <b>CAMBODIAN CHEMICAL SUPPLY CO., LTD.</b> |   | Doc No: TDS-PRD-009 |
|   | Doc Name                                   | <b>MAX EXTRA E Technical Data Sheet</b> | Revised No: 0       |
|   | Doc Type                                   | TDS                                     | Page: <b>3 of 3</b> |

**NOTE:**

*The above information is given to the best of our knowledge based on testing and practical application.*

*However, since we cannot anticipate or control the many conditions under which our products may be used, we can only guarantee the quality of the product itself. We reserve the right to alter the given data without prior notice.*

*Contact for further information:*  
*Mr. Vey Bora, Production Manager*  
*H/P: (+855) 15 888 003 / 78 885 443*  
*E-mail: [veybora@campaint-ccsc.com.kh](mailto:veybora@campaint-ccsc.com.kh)*