

# PAINTEX SUPER

## GENERAL INFORMATION

**PAINTEX SUPER** is a 100 % pure acrylic “*Matte Finish*” medium grade paint. It is specially formulated for all weathers. This medium grade paint is excellent adhesion on exterior (façade) and interior walls.

**PAINTEX SUPER** is good water resistant, very-good scrub resistant, resists fungus, flaking, chalking and it has been proven to be extremely durable through weathers.



<b>PRODUCT CLASSIFICATION</b>	<b>Matte Finish</b>	
<b>ADVANTAGES</b>	<ul style="list-style-type: none"> <li>• Good Hiding</li> <li>• Good-Workability</li> <li>• Low Odor</li> <li>• Anti-Fungal</li> <li>• Non- Mercury</li> </ul>	<ul style="list-style-type: none"> <li>• Crack Bridging</li> <li>• Good Adhesion</li> <li>• Long Lasting Color</li> <li>• Scrub Tolerance</li> </ul>
<b>USE</b>	<b>On</b>	Hard & soft boards, asbestos, ceilings, plaster, concrete and brickwork etc.
	<b>For</b>	Decoration and protection of the above stated substrate.
<b>COMPOSITION</b>	<b>Pigments</b>	Super Fine Titanium Dioxide & Mineral Extender
	<b>Binder</b>	100% Pure Acrylic Emulsion
	<b>Thinner</b>	Clean Water
<b>PROPERTIES</b>	<b>Color</b>	Multi Choices
	<b>Texture</b>	Matte Finish and Smooth
	<b>Specific Gravity</b>	1.40 +/- 0.05 Kg/ Liter
	<b>Recommended Dry Film Thickness per coat</b>	40-50μ
	<b>Drying Time</b>	Touch Dry: 15-30 minutes Hard Dry : 48 hours
	<b>Recoating Interval</b>	2 hours
	<b>Practical Coverage</b>	133 m <sup>2</sup> /pail /2coats
	<b>Packing Content</b>	18 Liters



# PAINTEX SUPER

<b>INSTRUCTION FOR USE</b>	<b>Surface Preparation</b>	Ensure that the surfaces are free from loose particles, dirt, dust, grease, oil, wax. Make good for any surface defected, clean thoroughly and dry.
	<b>Application Methods</b>	<p><b>By using Roller / Soft-Brush</b> Thin with some 10% of clean water and apply by using Roller and/or Soft-Brush.</p> <p><b>By using Air Spray</b> Dilute the paint with 20% of clean water.</p>
	<b>Previously Painted Surface</b>	Remove all unstable paint film, loose chalk, dust and other foreign matters. Treat surface with Cam-Paint Penetrate Primer “EVERLAST or PROTAN” to strengthen substrate condition.

RECOMMEND PAINT SYSTEM	Sequence	Application Product		No of Coat	For Old Substrate
		<i>Exterior</i>	<i>Interior</i>		
	Plaster	Vimean Sor/ King Plast	Vimean Sor/ King Plast	2 or 3	
	Primer	Prevalent	Prevalent	1	EVERLAST/ PROTAN
	Finish Coat	PAINTEX SUPER		2 or 3	

**NOTE:**

The above information is given to the best of our knowledge based on testing and practical application.

However, since we cannot anticipate or control the many conditions under which our products may be used, we can only guarantee the quality of the product itself. We reserve the right to alter the given data without prior notice.