

SARIKA

Wonder Hiding

GENERAL INFORMATION

SARIKA is GREEN EMULSION “High-Gloss” PREMIUM AQUEOUS PAINT. It is specially formulated for all weathers. This premium paint is excellent adhesion on exterior (facade) and interior walls.

SARIKA is a Water Resistant, Water Repellent, Excellent Scrub Resistant, resists fungus, flaking, chalking and it has been proven to be extremely durable through weathers.



ADVANTAGES	<ul style="list-style-type: none"> • Good Hiding • Well-Workability • High Gloss • Low Odor • Anti-Fungal 	<ul style="list-style-type: none"> • Non- Mercury • Crack Bridging • Excellent Adhesion • Long Lasting Color • Scrub Tolerance
	GRADE A	
PRODUCT CLASSIFICATION	GRADE A	
USE	<i>On</i>	Hard & soft boards, asbestos, ceilings, plaster, concrete and brickwork etc.
	<i>For</i>	Decoration and protection of the above stated substrate.
COMPOSITION	Pigments	80% Titanium Dioxide and 20% Specialty Kaolin
	Binder	100% Green Acrylic Emulsion – 50% of total volume
	Thinner	Clean Water
	Special Additive	Lead free, Ammonia Free, Formaldehyde Free, APEO free
PROPERTIES	Color	Multi Choices
	Texture	High-Gloss and Smooth
	Specific Gravity	1.23+/-0.02 Kg/ Liter
	Recommended Dry Film Thickness Per Coat	25-35μ
	Drying Time	Touch Dry: 20-30 minutes Hard Dry : 48 hours



SARIKA

Wonder Hiding

PROPERTIES	Recoating Interval	2 hours				
	Practical Coverage	155 m ² /pail/2coats				
	Pack Size	18 Liters				
INSTRUCTION FOR USE	Surface Preparation	Ensure that the surfaces are free from loose particles, dirt, dust, grease, oil, wax. Make good for any surface defected, clean thoroughly and dry.				
	Application Methods	<p>By using Roller / Soft-Brush Thin with some 10% of clean water and apply by using Roller and/or Soft-Brush.</p> <p>By Using Air Spray Dilute the paint with 20% of clean water.</p>				
	Previously Painted Surface	Remove all unstable paint film, loose chalk, dust and other foreign matters. Treat surface with Cam-Paint Penetrate Primer “EVERLAST or PROTAN” to strengthen substrate condition.				
RECOMMEND PAINT SYSTEM		Sequence	Application Product		No of Coat	For Old Substrate
			<i>Exterior</i>	<i>Interior</i>		
		Plaster	Grade A	Grade A	2 or 3	
		Primer	Grade A	Grade A	1	EVERLAST / PROTAN
	Finish Coat	SARIKA		2 or 3		

NOTE:

The above information is given to the best of our knowledge based on testing and practical application.

However, since we cannot anticipate or control the many conditions under which our products may be used, we can only guarantee the quality of the product itself. We reserve the right to alter the given data without prior notice.