

HOMY

GENERAL INFORMATION

HOMY is a pure acrylic-base Flat paint. It is specially formulated for all weathers conditions. This standard grade paint is good adhesion on exterior (façade) and interior walls. **HOMY** is water resistant, good scrub resistant, resists fungus, flaking, chalking and it has been proven to be extremely durable through weathers.



PRODUCT CLASSIFICATION	Flat Paint	
ADVANTAGES	<ul style="list-style-type: none"> • Good Hiding • Good-Workability • Low Odor • Anti-Fungal 	<ul style="list-style-type: none"> • Non- Mercury • Crack Bridging • Good Adhesion • Scrub Tolerance
USE	<p>On</p> <p>For</p>	<p>Hard & soft boards, asbestos, ceilings, plaster, concrete and brickwork etc.</p> <p>Decoration and protection of the above stated substrate.</p>
COMPOSITION	<p>Pigments</p> <p>Binder</p> <p>Thinner</p>	<p>Super Fine Titanium Dioxide & Mineral Extender</p> <p>Green Pure Acrylic Emulsion</p> <p>Clean Water</p>
PROPERTIES	<p>Color</p> <p>Texture</p> <p>Specific gravity</p> <p>Recommended Dry Film Thickness per coat</p> <p>Drying Time</p> <p>Recoating Interval</p> <p>Practical Coverage</p> <p>Packing Content</p>	<p>Multi Choices</p> <p>Matte Finish and Smooth</p> <p>1.40 +/- 0.05 Kg/Liter</p> <p>40-50μ</p> <p>Touch Dry: 15-30 minutes Hard Dry : 48 hours</p> <p>2 hours</p> <p>55 m²/pail/2coats</p> <p>26 Kgs</p>

HOMY

INSTRUCTION FOR USE	Surface Preparation	Ensure that the surfaces are free from loose particles, dirt, dust, grease, oil, wax. Make good for any surface defected, clean thoroughly and dry.				
	Application Methods	<p>By using Roller / Soft-Brush Thin with some 10% of clean water and apply by using Roller and/or Soft-Brush</p> <p>By Using Air Spray Dilute the paint with 20% of clean water.</p>				
	Previously Painted Surface	Remove all unstable paint film, loose chalk, dust and other foreign matters. Treat surface with Cam-Paint Penetrate Primer “EVERLAST or PROTAN” to strengthen substrate condition.				
RECOMMEN PAINT SYST		Sequence	Application Product		No of Coat	For Old Substrate
			<i>Exterior</i>	<i>Interior</i>		
		Plaster	Vimean Sor	BAN Ce.	2 or 3	
		Primer	Prevalent	Prevalent	1 or 2	EVERLAST/ PROTAN
	Finish Coat	HOMY		2 or 3		

NOTE:

The above information is given to the best of our knowledge based on testing and practical application.

However, since we cannot anticipate or control the many conditions under which our products may be used, we can only guarantee the quality of the product itself. We reserve the right to alter the given data without prior notice.